



☒ Targeted Search

☐ Records for: *Derwent World Patents*

[save as alert...](#)

[save strategy only...](#)

Output ☒

Format: **Full Record**

Output as: **Browser**

[display / send](#)

Modify ☒

[back to search](#)

[back to picklist](#)

select
☒ all ☐ none

Records 1 of 1 In full Format

1.

1/19/1

010108240 **Image available**

WPI Acc No: 1995-009493/199502

XRAM Acc No: C95-003624

XRPX Acc No: N95-007755

Colouring and transparency finishing for cement-based base material - by applying primer, intermediate coat and transparent pigment-contg. resin on base material

Patent Assignee: ASahi GLASS COAT & RESIN KK (ASAG)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 6293578	A	19941021	JP 93105193	A	19930407	199502 B

Priority Applications (No Type Date): JP 93105193 A 19930407

Patent Details:

Patent No	Kind	Lan Pg.	Main IPC	Filing Notes
JP 6293578	A	4	C04B-041/71	

Abstract (Basic): JP 6293578 A

Colouring and transparency finishing comprises: (a) applying a primer coating material on the cement-based base material; (b) applying an intermediate coating material comprising a synthetic resin coating material on the primer coating material; (c) applying a transparent pigment-contg. synthetic resin coating material as a finishing coating material on the intermediate coating material.

Pref. synthetic resin for the intermediate coating material contains a pigment having a refractive index of 1.4-1.7 and comprises a vinyl resin, acrylic resin, epoxy resin, polyurethane resin, chlorinated polyolefin resin, silicon.silicon cpd. or resin, polybutadiene, or fluoro-resin. The pigment having a refractive index of 1.4-1.7 comprises; e.g. asbestine, calcium carbonate, precipitating calcium carbonate, clay, kaolin. The synthetic resin for the finishing coating material comprises: a vinyl resin, acrylic resin, polyurethane resin, chlorinated polyolefin resin, silicon.silicon cpd. or resin, polybutadiene resin, or fluoro-resin. The pigment for the finishing coating material comprises; e.g. an azo dye, anthraquinone dye, indigo dye, phthalocyanine dye.

USE/ADVANTAGE - The finishing is for the cement-based base material. The method forms a coloured protective film without losing the quality of the cement-based base material.

Dwg.0/0

	実施例 1	実施例 2	比較例 1	比較例
下塗り塗料	アクアシール	アクアシール	アクアシール	アクアシ
中塗り塗料 合成樹脂	ルミフロン LF-200	ルミフロン LF-200	ルミフロン LF-200	ルミフロ LF-2
中塗り塗料 顔料と屈折率	硫酸バリウム 1.65	硫酸バリウム 1.65	硫酸バリウム 1.65	なし -
上塗り塗料 合成樹脂	ルミフロン LF-200	ルミフロン LF-200	ルミフロン LF-200	ルミフロ LF-2
上塗り塗料 顔料	赤系焼成	赤系べんがら	赤系べんがら	黄系黄
上塗り塗料 顔料粒子径	0.04 μm	0.04 μm	0.5 μm	0.5
試験体の外観	良好	良好	基材を隠蔽	濡れ肌色 基材を

Title Terms: COLOUR; TRANSPARENT; FINISH; CEMENT; BASED; BASE; MATERIAL;
APPLY; PRIME; INTERMEDIATE; COAT; TRANSPARENT; PIGMENT; CONTAIN; RESIN;
BASE; MATERIAL

Derwent Class: A82; G02; L02; P42; P64

International Patent Class (Main): C04B-041/71

International Patent Class (Additional): B05D-007/24; B28B-011/04;
C09D-127/12

File Segment: CPI; EngPI

Manual Codes (CPI/A-N): A08-E01; A08-M01; A12-B08; G02-A05E; G02-A05F;
L02-D14P

Polymer Indexing (PS):

<01>

001 017; P0088-R

002 017; P0500 F- 7A

003 017; P1445-R F81 Si 4A

004 017; P0464-R D01 D22 D42 F47

005 017; P1592-R F77 D01

006 017; R00806 G0828 G0817 D01 D02 D12 D10 D51 D54 D56 D58 D84; H0000;

P0328 ; P0339
007 017; ND01; Q9999 Q7114-R; Q9999 Q7158-R Q7114; K9698 K9676
008 017; K9574 K9483; K9610 K9483; B9999 B4397 B4240; K9870 K9847 K9790
009 017; R16211 D00 F80 O- 6A Si 4A; R01949 D00 F80 O- 6A Al 3A Si 4A;
R01278 D00 F44 C- 4A O- 6A Ca 2A; A999 A102 A077; B9999 B4444 B4240
010 017; A999 A033
<02>
001 017; P0088-R
002 017; P0500 F- 7A
003 017; P0464-R D01 D22 D42 F47
004 017; P1592-R F77 D01
005 017; P1445-R F81 Si 4A
006 017; R00806 G0828 G0817 D01 D02 D12 D10 D51 D54 D56 D58 D84; H0000;
P0328 ; P0339
007 017; ND01; Q9999 Q7114-R; Q9999 Q7158-R Q7114; K9698 K9676
008 017; K9574 K9483; K9712 K9676
009 017; D01 D18-R D25 D22 D35 D45 F13 F15 F23; A999 A102 A077
<03>
001 017; G0033-R G0022 D01 D02 D51 D53; H0000; H0011-R; M9999 M2244
M2222; P1150
002 017; ND01; Q9999 Q7114-R; Q9999 Q7158-R Q7114; K9698 K9676
003 017; K9574 K9483; K9610 K9483; B9999 B4397 B4240; K9870 K9847 K9790
004 017; Cl 7A; H0157
005 017; R16211 D00 F80 O- 6A Si 4A; R01949 D00 F80 O- 6A Al 3A Si 4A;
R01278 D00 F44 C- 4A O- 6A Ca 2A; A999 A102 A077; B9999 B4444 B4240
006 017; A999 A033
<04>
001 017; G0033-R G0022 D01 D02 D51 D53; H0000; H0011-R; M9999 M2244
M2222; P1150
002 017; ND01; Q9999 Q7114-R; Q9999 Q7158-R Q7114; K9698 K9676
003 017; K9574 K9483; K9712 K9676
004 017; Cl 7A; H0157
005 017; D01 D18-R D25 D22 D35 D45 F13 F15 F23; A999 A102 A077
Derwent Registry Numbers: 1278-U; 1949-U

Derwent WPI (Dialog® File 351): (c) 2004 Thomson Derwent. All rights reserved.

©1997-2004 Dialog, a Thomson business - Version 2.3